



## Technical Specifications GP-0 110 A EVO | M.Y 2025

<b>ENGINE TYPE</b>	ZS 110 cc horizontal single cylinder 4 stroke, Air Cooling
<b>VALVE ACTUATION</b>	Single camshaft, SOHC - 2 valves
<b>FUEL</b>	Unleaded Petrol (N.O. min 95)
<b>BORE &amp; STROKE</b>	52,4mm x 49,5mm
<b>DISPLACEMENT</b>	106,7 cc
<b>FUEL SYSTEM</b>	Carburetor KF PZ19 (oval section 13x18), Racing air filter
<b>IGNITION</b>	Electronic, external spark plug & coil
<b>STARTER</b>	Electric
<b>EXHAUST SYSTEM</b>	Exhaust pipe in stainless steel. Under saddle single silencer Arrow in titanium. Ready for DB Killer
<b>LUBRICATION</b>	Wet sump lubrication system, with oil radiator. Oil quantity: 0,9 Liter
<b>TRANSMISSION</b>	Automatic   Ohvale setting
<b>PRIMARY DRIVE</b>	Gears
<b>SECONDARY DRIVE</b>	Regina chain gold series. Drive ratio 17/32 (1,882)
<b>CLUTCH</b>	Centrifugal clutch
<b>FRAME</b>	High-strength steel trellis frame, robotic welding (New config. 2025)
<b>FRONT SUSPENSION</b>	Ø 33mm upside-down fork & CNC foot fork. Spring config. K6-K6
<b>REAR SUSPENSION</b>	Aluminium swing-arm. Monoshock with piggy-back. Fully adjustable: hydraulic compression and rebound damping, spring preload & wheelbase. Spring config. K140
<b>FOOTREST</b>	CNC machined parts
<b>FRONT BRAKING SYSTEM</b>	Single disc Ø 180mm. Formula monoblock radial caliper (4 pistons D24). Sintered brake pads. Axial master cylinder with integrated tank & braided steel hose
<b>REAR BRAKING SYSTEM</b>	Single disc Ø 155mm. Formula radial caliper (2 pistons D24). Master cylinder with integrated tank & braided steel hose
<b>RIMS</b>	Aluminium alloy wheels, design by Ohvale. Front 2,50 x 10" - Rear 3,00 x 10"
<b>TYRES</b>	Tubeless Pirelli slick. Front 100/80 - 10", Rear 120/80 - 10"
<b>FAIRINGS</b>	Fiberglass racing fairings + New graphic design 2025
<b>DIMENSIONS (DEFAULT SETTINGS)</b>	Max. length: 1478mm / Max. width: 630mm (at the handlebar) Max. height: 790mm / Saddle height 695mm
<b>DRY WEIGHT</b>	67 Kg (without any liquid)
<b>FUEL TANK CAPACITY</b>	3,5 Liters

■ New features Model Year 2025