



| | |
|-------------------------------|---|
| ENGINE TYPE | Daytona 190 cc horizontal single cylinder 4 stroke, Air Cooling |
| VALVE ACTUATION | Single camshaft, SOHC - 4 valves |
| FUEL | Unleaded Petrol (N.O. min 95) |
| BORE & STROKE | 62mm x 62mm |
| DISPLACEMENT | 187,18 cc |
| FUEL SYSTEM | Carburetor DELLORTO PHBH 28 BD Ohvale Settings, Racing air filter |
| IGNITION | Electronic, external spark plug & coil (CDI with Rev Limiter) |
| STARTER | Kick starter with decompression system |
| EXHAUST SYSTEM | Exhaust pipe in stainless steel. Under saddle single silencer Arrow in titanium. Ready for DB Killer |
| LUBRICATION | Wet sump lubrication system, with oil radiator. Oil quantity: 1 Liter |
| TRANSMISSION | 4 Speed, N - 1 - 2 - 3 - 4 Ohvale setting |
| PRIMARY DRIVE | Gears |
| SECONDARY DRIVE | Regina chain gold series. Ergal Sprocket. Drive ratio 17/36 (2,117) |
| CLUTCH | STANDARD: 6 Plate wet clutch RACE: Dedicated slipper clutch system |
| FRAME | High-strength steel trellis frame, robotic welding (New config. 2025) |
| FRONT SUSPENSION | STANDARD: Ø 33mm upside-down fork & CNC foot fork. Spring config. K7-K7 and adjustable spring preload PRO/RACE: Ø 35mm fully adjustable Ohvale racing fork. Spring config. K7-K8 |
| REAR SUSPENSION | Aluminium swing-arm. Monoshock with piggy-back. Fully adjustable: hydraulic compression and rebound damping, spring preload & wheelbase. Spring config. K140 |
| FOOTREST | STANDARD: CNC machined parts RACE: Standard config. + Electronic quickshifter |
| FRONT BRAKING SYSTEM | STANDARD: Single floating disc Ø 220mm, 4.5mm tk. Brembo radial caliper (4 pistons D24). Sintered brake pads. Brembo axial master cylinder PS 10/19 with integrated tank & braided steel hose PRO/RACE: Standard config. + Floating disc Ø 230mm, 4.5mm tk |
| REAR BRAKING SYSTEM | Single disc Ø 180mm. J. Juan floating caliper (single piston D25). Axial master cylinder with integrated tank & braided steel hose |
| RIMS | Aluminum alloy wheels, design by Ohvale. Front 2,50 × 12" - Rear 3,00 × 12" |
| TYRES | Tubeless Pirelli slick. Front 100/90 - 12", Rear 120/80 - 12" |
| FAIRINGS | Fiberglass racing fairings + New graphic design 2025 |
| DIMENSIONS (DEFAULT SETTINGS) | Max. length: 1610mm / Max. width: 740mm (at the handlebar) Max. height: 915mm / Saddle height 725mm |
| DRY WEIGHT | 71 Kg (without any liquid) |
| FUEL TANK CAPACITY | 3,5 Liters |

■ New features Model Year 2025